

Serial No.: Pending
Examiner: Ghafoorian, Roz
Art Unit: 3763

AMENDMENTS TO THE CLAIMS

Claims 1-30 (Cancelled)

31. (Original) A device for delivering fluid to a patient, comprising:

an exit port assembly;

a dispenser including,

a container having an outlet connected to the exit port assembly, an inlet for connection to a reservoir, and a side wall extending along a longitudinal axis towards the outlet and the inlet, and

a plunger assembly received in the container and including,

a first lateral segment extending laterally with respect to the longitudinal axis of the container and contacting the side wall of the container,

a second lateral segment positioned between the first lateral segment and the outlet of the container, the second lateral segment extending laterally with respect to the longitudinal axis of the container and contacting the side wall of the container, and longitudinally spaced from the first lateral segment, and

a shape memory element having a changeable length decreasing from an uncharged length to a charged length when at least one charge is applied to the shape memory element, the shape memory element connecting the first and the second lateral segments.

Serial No.: Pending
Examiner: Ghafoorian, Roz
Art Unit: 3763

32. (Original) A device according to claim 31, wherein the shape memory element is made of a nickel and titanium alloy.

33. (Original) A device according to claim 31, wherein the shape memory element is elongated and extends between a first end connected to the first lateral segment and a second end connected to the second lateral segment.

34. (Original) A device according to claim 33, wherein the shape memory element comprises a wire having a generally circular cross-section.

35. (Original) A device according to claim 33, wherein the shape memory element comprises a coiled spring.

36. (Original) A device according to claim 33, wherein the shape memory element comprises a collapsible bellows.

37. (Original) A device according to claim 31, wherein the plunger assembly further includes a rigid projection positioned between the first and the second lateral segments and extending parallel with the longitudinal axis of the container for limiting the closeness of the first and the second lateral segments.

38. (Original) A device according to claim 37, wherein the rigid projection of the plunger assembly has a substantially predetermined length extending parallel with the longitudinal axis of the container.

Serial No.: Pending
Examiner: Ghafoorian, Roz
Art Unit: 3763

39. (Original) A device according to claim 38, wherein the shape memory element has a substantially predetermined uncharged length.

40. (Original) A device according to claim 31, wherein the shape memory element has a substantially predetermined uncharged length and a substantially predetermined charged length.

41. (Original) A device according to claim 31, wherein the plunger assembly is prevented from rotating with respect to the side wall of the container.

42. (Original) A device according to claim 31, wherein the first lateral segment is fixed in position with respect to the side wall of the container.

43. (Original) A device according to claim 31, wherein the plunger assembly further includes a cooler assembly in contact with the shape memory element.

44. (Original) A device according to claim 43, wherein the cooler assembly includes a thermoelectric cooler.

45. (Original) A device according to claim 43, wherein the cooler assembly includes a heat sink.

46. (Original) A device according to claim 31, wherein the container includes a check valve assembly within the outlet.

Serial No.: Pending
Examiner: Ghafoorian, Roz
Art Unit: 3763

47. (Original) A device according to claim 31, wherein the container includes a check valve assembly within the inlet.

48. (Original) A device according to claim 31, wherein:

the side wall of the container includes a first section extending from the outlet and the inlet of the container parallel with the longitudinal axis and a second section extending from the first section parallel with the longitudinal axis, and wherein the first section of the side wall has an internal cross-sectional dimension that is unequal to an internal cross-sectional dimension of the second section of the side wall; and

the first and the second lateral segments of the plunger assembly are received in the second section of the side wall of the container, and the plunger assembly further includes strut extending from the second lateral segment and slidingly received in the first section of the side wall of the container, wherein the strut is sized and shaped to provided a substantially fluid-tight seal between the first section of the side wall and the strut.

49. (Original) A device according to claim 31, further comprising a reservoir connected to the inlet of the dispenser.

50. (Original) A device according to claim 49, wherein the reservoir contains a therapeutic fluid.

51. (Original) A device according to claim 50, wherein the therapeutic fluid is insulin.

Serial No.: Pending
Examiner: Ghafoorian, Roz
Art Unit: 3763

52. (Original) A device according to claim 31, wherein the exit port assembly includes a transcutaneous patient access tool.

53. (Original) A device according to claim 52, wherein the transcutaneous patient access tool comprises a needle.

54. (Original) A device according to claim 31, further comprising a local processor connected to ends of the shape memory element through conductive wires and programmed to provide charges to the shape memory element based upon flow instructions.

55. (Original) A device according to claim 54, further comprising a power supply connected to the local processor.

56. (Original) A device according to claim 31, further comprising:

- a local processor electrically connected to the shape memory element of the plunger assembly and programmed to provide electrical charges to the shape memory element based upon flow instructions;
- a wireless receiver connected to the local processor for receiving flow instructions from a separate, remote control device and delivering the flow instructions to the local processor;
- and
- a housing containing the dispenser, the exit port assembly, the local processor and the wireless receiver, and wherein the housing is free of user input components for providing flow instructions to the local processor.

Serial No.: Pending
Examiner: Ghafoorian, Roz
Art Unit: 3763

57. (Original) A system including a fluid delivery device according to claim 56, and further comprising a remote control device separate from the fluid delivery device and including:

a remote processor;

user interface components connected to the remote processor for allowing a user to provide flow instructions to the remote processor; and

a transmitter connected to the remote processor for transmitting the flow instructions to the receiver of the fluid delivery device.

58. (Original) A device according to claim 31, wherein the shape memory element comprises two-way shape memory material and the shape memory element biases the first and the second lateral segments together when at least one charge is applied to the shape memory element and biases the first and the second lateral segments apart when at least one charge is removed.

59. (Original) A device according to claim 31, wherein the shape memory element comprises one-way shape memory material and biases the first and the second lateral segments together when at least one charge is applied to the shape memory element.

60. (Original) A device according to claim 59, wherein the plunger assembly further includes a spring biasing the first and the second lateral segments.

Serial No.: Pending
Examiner: Ghafoorian, Roz
Art Unit: 3763

61. (Original) A device for delivering fluid to a patient, comprising:

an exit port assembly;

a dispenser including,

a container having an outlet connected to the exit port assembly, an inlet for connection to a reservoir, and a side wall extending along a longitudinal axis towards the outlet and the inlet, and

a plunger assembly received in the container and including,

a first lateral segment extending laterally with respect to the longitudinal axis of the container and contacting the side wall of the container,

a second lateral segment positioned between the first lateral segment and the outlet of the container, the second lateral segment extending laterally with respect to the longitudinal axis of the container and contacting the side wall of the container, and longitudinally spaced from the first lateral segment,

a spring biasing the first and the second lateral segments longitudinally apart, and

an actuator arranged to overcome the spring and bias the first and the second lateral segments longitudinally together upon actuation.

Serial No.: Pending
Examiner: Ghafoorian, Roz
Art Unit: 3763

62. (Original) A device according to claim 61, wherein the plunger assembly further includes a rigid projection positioned between the first and the second lateral segments and extending parallel with the longitudinal axis of the container for limiting the closeness of the first and the second lateral segments.

63. (Original) A device according to claim 62, wherein the rigid projection of the plunger assembly has a substantially predetermined length extending parallel with the longitudinal axis of the container.

64. (Original) A device according to claim 61, wherein the plunger assembly is prevented from rotating with respect to the side wall of the container.

65. (Original) A device according to claim 61, wherein the first lateral segment is fixed in position with respect to the side wall of the container.

66. (Original) A device according to claim 61, wherein the container includes a check valve assembly within the outlet.

67. (Original) A device according to claim 61, wherein the container includes a check valve assembly within the inlet.

Serial No.: Pending
Examiner: Ghafoorian, Roz
Art Unit: 3763

68. (Original) A device according to claim 61, wherein:

the side wall of the container includes a first section extending from the outlet and the inlet of the container parallel with the longitudinal axis and a second section extending from the first section parallel with the longitudinal axis, and wherein the first section of the side wall has an internal cross-sectional dimension that is unequal to an internal cross-sectional dimension of the second section of the side wall; and

the first and the second lateral segments of the plunger assembly are received in the second section of the side wall of the container, and the plunger assembly further includes strut extending from the second lateral segment and slidingly received in the first section of the side wall of the container, wherein the strut is sized and shaped to provided a substantially fluid-tight seal between the first section of the side wall and the strut.

69. (Original) A device according to claim 61, further comprising a reservoir connected to the inlet of the dispenser.

70. (Original) A device according to claim 69, wherein the reservoir contains a therapeutic fluid.

71. (Original) A device according to claim 70, wherein the therapeutic fluid is insulin.

72. (Original) A device according to claim 61, wherein the exit port assembly includes a transcutaneous patient access tool.

Serial No.: Pending
Examiner: Ghafoorian, Roz
Art Unit: 3763

73. (Original) A device according to claim 72, wherein the transcutaneous patient access tool comprises a needle.

74. (Original) A device according to claim 61, further comprising a local processor connected to the actuator of the plunger assembly and programmed to actuate the actuator based upon flow instructions.

75. (Original) A device according to claim 74, further comprising a power supply connected to the local processor.

76. (Original) A device according to claim 61, further comprising:

- a local processor electrically connected to the actuator of the plunger assembly and programmed to actuate the actuator based upon flow instructions;
- a wireless receiver connected to the local processor for receiving flow instructions from a separate, remote control device and delivering the flow instructions to the local processor; and
- a housing containing the dispenser, the exit port assembly, the local processor and the wireless receiver, and wherein the housing is free of user input components for providing flow instructions to the local processor.

Serial No.: Pending
Examiner: Ghafoorian, Roz
Art Unit: 3763

77. (Original) A system including a fluid delivery device according to claim 76, and further comprising a remote control device separate from the fluid delivery device and including:

a remote processor;

user interface components connected to the remote processor for allowing a user to provide flow instructions to the remote processor; and

a transmitter connected to the remote processor for transmitting the flow instructions to the receiver of the fluid delivery device.

78. (Original) A device according to claim 61, wherein the actuator of the plunger assembly comprises a piezoelectric element.

79. (Original) A device according to claim 61, wherein the actuator of the plunger assembly comprises a solenoid assembly.

80. (Cancelled)

81. (Cancelled)

82. (Original) A device according to claim 48, wherein the internal cross-sectional dimension of the first section of the side wall of the container is smaller than the internal cross-sectional dimension of the second section of the side wall.

Serial No.: Pending
Examiner: Ghafoorian, Roz
Art Unit: 3763

83. (Original) A device according to claim 68, wherein the internal cross-sectional dimension of the first section of the side wall of the container is smaller than the internal cross-sectional dimension of the second section of the side wall.